




# BLUE MONSTER® Stay-Soft Sealant



## Stay-Soft PTFE Pipe Thread Sealant



**Stay-Soft Thread Sealant with PTFE**

**Formulated for the fire protection industry.**

*For use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.*



Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly.

Suitable for use on all threaded connections, Stay-Soft is recommended for on-site or assembly line work. It is lead-free, non-toxic and when properly used, will perform in accordance with applicable standards.

Blue Monster Stay-Soft is made with the highest quality materials. All information provided is based on our laboratory testing, independent laboratory test results and actual field experience. Since we are unable to control conditions for which the product is being used, our only obligation will be the replacement of the compound.

- Grit-Free
- Non-Drying
- Non-Separating
- Adheres to oily threads
- Non-Toxic
- Easy-cleanup

Suitable for use on systems carrying:  
Air; Glycerine; Glycol; Steam;  
Water (hot or cold).



FBC™ System Compatible indicates that this product has been submitted by the manufacturer for testing, and is monitored on an ongoing basis to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. The manufacturer also agrees not to change the product after passing the test. FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

Cat #	Size	Case Pack	Weight
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / 946 ml	12	50 lbs (22.7 kg)

Brushable from -15°F (-26°C) to +400°F (204°C)  
Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm<sup>2</sup>)  
Liquids up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)  
Blue Monster Stay Soft exceeds US Federal Specification TT-S-1732

For Material Safety Data Sheets, contact Mill-Rose or download directly from the Mill-Rose Clean-Fit website.

**The Mill-Rose Company • Clean-Fit Products**  
7310 Corporate Blvd., Mentor, OH 44060

To order call toll-free: (800) 321-3598 or Fax: (440) 255-1072

Visit our web site at [www.CleanFit.com](http://www.CleanFit.com) • E-mail: [info@CleanFit.com](mailto:info@CleanFit.com)